



Innovative engineered design, development and manufacturing of quality quarter turn valves and automation products that optimize uptime and ensure lower overall cost of ownership

INDUSTRY APPLICATIONS

AGRICULTURE & IRRIGATION • AUTOMOTIVE • CEMENT • CHEMICAL & PETROCHEMICAL • DESALINATION • FERTILIZERS • FOOD & BEVERAGE • HVAC • INDUSTRIAL & PSA PLANTS • MINING • OIL & GAS • PAINTS • PHARMACEUTICAL • POWER/FGD • PULP & PAPER • REFINERY • SHIPBUILDING/MARINE • STEEL & PRIMARY METALS • TEXTILE • TRANSPORTATION • WATER/WASTEWATER

delvalflow.com

1-833-DELVAL1



WHO WE ARE

Founded in 2006, **DelVal Flow Controls** provides a wide range of superior quality ball valves, butterfly valves, actuators and control accessories by implementing a robust quality management system compliant to ISO 9001-2015 and cultivating a knowledgeable staff. Our products are fully integrated and cater to a wide spectrum of applications including Oil & Gas, Power Generation, Mining, Chemical Process, Marine, Pharmaceutical, Food & Beverage, Water and other industrial markets. Our global network of offices, distributors, channel partners and highly experienced sales and service staff are always ready to meet our customers' most stringent requirements.

BUTTERFLY VALVES

Center-LOK® Seat Designin Resilient Seated Butterfly Valves

- Heavy-duty, square grooved design that ensures rigid locking of seat in body preventing seat movement
- · Fully rated for dead-end and vacuum service



Series 51/53

Large Diameter Resilient Seated 26" to 40" (DN 650 – DN 1000) 150 PSIG (PN 10), 50 PSIG (PN 3.5)



Series 55

Double Offset Resilient Seated 3" to 88" (DN 80 – DN 2200) 150 PSIG (PN 10), 230 PSIG (PN 16)



Series 50/52

Resilient Seated

2" to 24" (DN 50 - DN 600)

2" to 12"- 175 PSIG (PN12), 230 PSIG (PN 16), 150 PSIG (PN 10), 50 PSIG (PN 3.5)

14" to 24" – 150 PSIG (PN 10), 230 PSIG

(PN 16), 50 PSIG (PN 3.5)



Series 5C/5D

Split Body Resilient Seated 2" to 24" (DN 50 – DN 600) 150 PSIG (PN 10)



Series 42/43

Lined, PTFE / PFA 2" to 24" (DN 50 – DN 600) 150 PSIG (PN 10)



Series 44-49

High Performance Double Offset 2" to 48" (DN 50 – DN 1200)

2" to 48" - Class 150; 2" to 24" - Class 300



Series 4

Triple Offset

3" to 48" (DN 80 – DN 1200) 3" to 48" - Class 150;

3" to 24" - Class 300 / 600

BALL VALVES

ULTRA Seat Material in Ball Valves and High Performance Butterfly Valves

- Engineered polymer that is rated for max 500°F (260°C) at 285 PSIG for HPBV and 390°F (200°C) at 150 PSIG for Ball Valve
- Excellent for handling aggressive fluids at high temperatures



Series F

Oil & Gas Floating Ball Valve 2" to 8" (DN 50 - DN 200) Class 150 to Class 1500 in full and reduced ports



Series 7/8

Trunnion Mounted Ball Valve Series 7 2" to 14" (DN 50 - DN 350) in Two-Piece Body Series 8 16" to 24" (DN 400 - DN 600) in Three-Piece Body Class 150 to Class 1500 in full and reduced ports



Series 2000

Seal Welded Valve 1/2" to 2" (DN 15 - DN 50) 2000 PSIG (WOG)



Series 65-72

Floating Ball Valve 1/2" to 12" (DN 15 - DN 300) Class 150 to Class 900 in full and reduced ports

AUTOMATION

Universal Insert Design in Pneumatic Actuators

- · Allows direct mounting of DelTorg actuators to most quarter-turn valves
- Eliminates the use of brackets and couplings saves time and money



Pneumatic Rack & Pinion



Series 92/93 Insert



Series 2E Electric Actuator



Limit Switch Box



Series 85 Solenoid Valve



Series 87 Positioner



100% TESTING 100% SERIALIZATION



CERTIFICATES





















Manufacturing & Sales - Americas DelVal Flow Controls USA

6068 Highway 73 Geismar, Louisiana 70734 | USA T: +1 833-DELVAL1 F: +1 225-744-4328 sales@delvalflow.com

Manufacturing & Sales - International DelVal Flow Controls Pvt. Ltd.

Gat No: 25, Kavathe Post-Javale, Tal. Khandala Dist.Satara Pin-412801 | India salesindia@delvalflow.com

International Projects DelVal Flow Controls USA

11767 Katy Freeway, Suite 435 Houston, Texas 77079 | USA T: +1 281-809-3652 projects@delvalflow.com

delvalflow.com